

Product data sheet

Item No. 92.238.2014.3

Cable assembly GST18I3K1-S 25W 20GR01

geis® Connection cable male - free end; length: 2m; type GST18I3; 3-pole; 250 V / 20 A; colour of coding: grey with grey strain-relief; cable:H05V2V2-F 3G2,5, colour: black



Item No.	92.238.2014.3
EAN	4015573856158
Order Unit	25 Piece(s)

Certificates / Approvals

Technical data

General

Rated current	20 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	2
Mechanical coding	Code 2
Interlockable	Yes
Color of coding/ contact carrier	Pebble gray
Marking of poles	
Color of housing inclusive strain relief	Pebble gray

Model

Number of poles	3
Nominal cross section conductor	2.5 mm²
Degree of protection (IP)	IP40
Wire strip length	9 mm
sheath strip length	35 mm
Preparation of conductor ends	Ultrasonically compressed wire ends
Cable type	H05V2V2-F
Cable colour	Black
Cable diameter	10.2 mm

Version of cable	Male - free end
Type of cord set	Connection cable
Version cable end 2	Free end

Material

Surface finish	Tin-plated
Halogen free	No
Continuous temperature of cable	90 °C
Insulation components continuous temperature	100 °C

Dimensions

Total length	2 m
--------------	-----