

## Product data sheet

Item No. 92.238.2500.2

### Cable assembly

geis® Extension cable female - male; length: 2,5m; type GST18I3; 3-pole; 250 V / 20 A; colour of coding: white with white strain-relief; cable: H05VV-F 3G2,5, colour: white



|            |               |
|------------|---------------|
| Item No.   | 92.238.2500.2 |
| EAN        | 4015573534803 |
| Order Unit | 20 Piece(s)   |

### Certificates / Approvals



### Technical data

#### General

|                                          |        |
|------------------------------------------|--------|
| Rated current                            | 20 A   |
| Rated voltage                            | 250 V  |
| Rated impulse voltage                    | 4 kV   |
| Pollution degree                         | 2      |
| Mechanical coding                        | Code 1 |
| Interlockable                            | Yes    |
| Color of coding/ contact carrier         | White  |
| Marking of poles                         |        |
| Color of housing inclusive strain relief | White  |

#### Model

|                                 |               |
|---------------------------------|---------------|
| Number of poles                 | 3             |
| Nominal cross section conductor | 2.5 mm²       |
| Degree of protection (IP)       | IP40          |
| Cable type                      | H05VV-F       |
| Cable colour                    | White         |
| Cable diameter                  | 10.2 mm       |
| Version of cable                | Female - male |

|                     |                  |
|---------------------|------------------|
| Type of cord set    | Connecting cable |
| Version cable end 1 | GST18i3 socket   |
| Version cable end 2 | GST18i3 plug     |

#### Material

|                                              |            |
|----------------------------------------------|------------|
| Surface finish                               | Tin-plated |
| Halogen free                                 | No         |
| Continuous temperature of cable              | 70 °C      |
| Insulation components continuous temperature | 100 °C     |

#### Dimensions

|              |       |
|--------------|-------|
| Total length | 2.5 m |
|--------------|-------|

#### Technical drawing

