

Product data sheet

Item No. 92.238.5000.5

Cable assembly GST18I3K1BS 25 50RT03

geis® Extension cable female - male; length: 5m; type GST18I3;
3-pole; 250 V / 20 A; colour of coding: red with red strain-relief;
cable: H05VV-F 3G2,5, colour: black



Item No.	92.238.5000.5
EAN	4015573681217
Order Unit	10 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	20 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	2
Mechanical coding	Code 3
Interlockable	Yes
Color of coding/ contact carrier	Salmon pink
Marking of poles	
Color of housing inclusive strain relief	Salmon pink

Model

Number of poles	3
Nominal cross section conductor	2.5 mm ²
Degree of protection (IP)	IP40
Cable type	H05VV-F
Cable colour	Black
Cable diameter	10.2 mm
Version of cable	Female - male

Type of cord set	Connecting cable
Version cable end 1	GST18i3 socket
Version cable end 2	GST18i3 plug


Material

Surface finish	Tin-plated
Halogen free	No
Continuous temperature of cable	60 °C
Insulation components continuous temperature	100 °C

Dimensions

Total length	5 m
--------------	-----

Technical drawing



Buchse/teil/female connector

Stecker/teil/male connector

Kabel/cable: H05VV-F3G2,5
Farbe/colour: siehe Tabelle/see table

Gesamtlänge / total length

.F	Farbe colour	Codierung •X• Buchse female	Codierung •Y• Stecker male	Kabelfarbe cable colour
.1	schwarz black			schwarz black
.2	weiß white			weiß white
.3	grau grey			schwarz black
.5	rot red			schwarz black

Teile-Nr.
part-no.

L	Beispiel (Farbe: schwarz) example (colour: black)	Typ type
92.238.XX00.F	XX in dm-Schritten 92.238.1000.1 = 10dm/L = 1000mm	GST18i3K1BS 25 10SW
U2.238.XX00.F	XX in m-Schritten U2.238.1200.1 = 12 m/L = 12000mm	GST18i3K1BS 25 X12SW

Typ/type: GST18i3K1BS 25 ..

SW = schwarz/black
WS = weiß/white
GR01 = grau/grey
RT03 = rot/red

Further data see catalog

Wieland logo

PRE-ASSEMBLED CABLE
KONFEKT-LEITUNG

Buchse/female-Stecker/male Crimpversion K1
(a) 250V AC 20A 2,5sqmm