

Product data sheet

Item No. 96.222.2003.1

Cable assembly RST20I2K1B- 15P 20SW

Connection cable, female - free end, length 2m, RST20i2, 2 pole, 250V, 16A, cable type H05VV, cross section 1,5mm², color of coding: black



Item No.	96.222.2003.1
EAN	4015573927827
Order Unit	50 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	16 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	3
Mechanical coding	Yes
Interlockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	
Color of housing inclusive strain relief	Black

Model

Number of poles	2
Nominal cross section conductor	1.5 mm ²
Degree of protection (IP)	IP66/IP68
Wire strip length	9 mm
sheath strip length	35 mm
Preparation of conductor ends	Ultrasonically compressed wire ends
Cable type	H05VV-F

Cable colour	Black
Cable diameter	7.5 mm
Version of cable	Female - free end

Material

Surface finish	Silver-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continous temperature	100 °C

Dimensions

Total length	2 m
--------------	-----

Technical drawing

.F	Farbe colour	Codierung *U*
.0	lichtgrau light grey	N
.1	schwarz black	L

Typ: RST2012K1B- 15P .. GL = lichtgrau/light grey
SW = schwarz/black

Teile-Nr. part-no.	L	Beispiel (Farbe: schwarz, lichtgrau) example (colour: black, grey)	Typ type
96.222.XX03.1	XX in dm-Schritten	96.222.1003.1 = 10dm/L= 1000mm	RST2012K1B- 15P 10SW
96.222.XX03.0		96.222.1003.0	RST2012K1B- 15P 10GL
U6.222.XX03.1	XX in m-Schritten	U6.222.1203.1 = 12 m/L=12000mm	RST2012K1B- 15P X12SW
U6.222.XX03.0		U6.222.1203.0	RST2012K1B- 15P X12GL

Freitoleranz nach DIN 15901, IS 120		CAD - Zeichnung, keine manuellen Änderungen		1. Verwendung:	
Modus	Werkstoff und Oberfläche:	2005	Tag	Name	Zeichnung Nr.
/		Erstellt	Gr.-Bl.	Revisio	96.222.0403.0 01K a
/		Geprüft			
/		Bel.	mit	mit	
/		Gepr.			
/		Bel.			

KONFEKT-LEITUNG
cord grip/ crimp design KI 250V 16A
Crimpausführung KI 250V 16A