



Product data sheet

Item No. 96.032.2153.0

Male connector RST20I3F S2 M03V GL

Device connectors, modular M16, RST20i3, 3 pole, straight, male, spring clamp connection, 250V/20A, color of coding: light gray, color of housing: light gray



Item No.	96.032.2153.0
EAN	4015573895386
Order Unit	100 Piece(s)

Certificates / Approvals







Technical data

General

Rated current	20 A
Rated voltage	250 V
Pollution degree	3
Mechanical coding	Yes
Rated impulse voltage	4 kV
Interlockable	Yes
Color of coding/ contact carrier	Light grey
Marking of poles	
Color of separate adapter (if present)	Light grey

Connection Data

Connection cross section solid	2.5 mm ²
Connection cross section stranded	1.5 mm²
Terminations per pole	2

Model

Model	male
Number of poles	3





Connection type	Tension clamp connection
Connecting thread metric	M16
Angle of plug	Straight
Degree of protection (IP)	IP66/IP68
Remark to type of connection	Finely stranded con. req. Wieland cable end sleeve
Built-in component	Snap-in/screw-in

Material

Housing material	Polyamide
Halogen free	Yes
Contact material	CuZn
Insulation components continous temperature	100 °C
Surface finish	Silver-plated

Dimensions

Length	68.3 mm
Width	35 mm
Height	35 mm

Technical drawing

