



Product data sheet

Item No. 96.232.4006.7

Cable assembly RST20I3K1-S 15PH 40GN02

Connection cable, male - free end, length 4m, RST20i3, 3 pole, 250/400V, 16A, cable type H05VV, cross section 1,5mm², color of coding: green



| Item No. | 96.232.4006.7 |
|------------|---------------|
| EAN | 4015573916388 |
| Order Unit | 20 Piece(s) |

Certificates / Approvals



Technical data

General

| Rated current | 16 A |
|--|-------|
| Rated voltage | 400 V |
| Rated impulse voltage | 4 kV |
| Pollution degree | 3 |
| Mechanical coding | Yes |
| Interlockable | Yes |
| Color of coding/ contact carrier | Green |
| Marking of poles | |
| Color of housing inclusive strain relief | Black |

Model

| 3 | | |
|-------------------------------------|--|--|
| 1.5 mm ² | | |
| IP66/IP68 | | |
| 9 mm | | |
| 35 mm | | |
| Ultrasonically compressed wire ends | | |
| H05VV-F | | |
| | | |





| Cable colour | Black |
|------------------|-----------------|
| Cable diameter | 8.3 mm |
| Version of cable | Male - free end |

Material

| Surface finish | Silver-plated |
|---|---------------|
| Halogen free | No |
| Continuous temperature of cable | 70 °C |
| Insulation components continous temperature | 100 °C |

Dimensions

| Total length | 4 m | |
|--------------|-------|--|
| Total length | 7 !!! | |

Technical drawing

