

## Product data sheet

Item No. 96.232.2003.1

### Cable assembly RST20I3K1B- 15P 20SW

Connection cable, female - free end, length 2m, RST20i3, 3 pole, 250V, 16A, cable type H05VV, cross section 1,5mm<sup>2</sup>, color of coding: black



|            |               |
|------------|---------------|
| Item No.   | 96.232.2003.1 |
| EAN        | 4015573761254 |
| Order Unit | 50 Piece(s)   |

## Certificates / Approvals



## Technical data

### General

|                                          |       |
|------------------------------------------|-------|
| Rated current                            | 16 A  |
| Rated voltage                            | 250 V |
| Rated impulse voltage                    | 4 kV  |
| Pollution degree                         | 3     |
| Mechanical coding                        | Yes   |
| Interlockable                            | Yes   |
| Color of coding/ contact carrier         | Black |
| Marking of poles                         |       |
| Color of housing inclusive strain relief | Black |

### Model

|                                 |                                     |
|---------------------------------|-------------------------------------|
| Number of poles                 | 3                                   |
| Nominal cross section conductor | 1.5 mm <sup>2</sup>                 |
| Degree of protection (IP)       | IP66/IP68                           |
| Wire strip length               | 9 mm                                |
| sheath strip length             | 35 mm                               |
| Preparation of conductor ends   | Ultrasonically compressed wire ends |
| Cable type                      | H05VV-F                             |

