

## Product data sheet

Item No. 96.454.3033.1

### Cable assembly RST20I5KSB- 40 30SW

Connection cable, female - free end, length 3m, RST20i5, 5 pole, 250/400V, 20A, cable type H07RN-F, cross section 4,0 mm<sup>2</sup>, color of coding: black



|            |               |
|------------|---------------|
| Item No.   | 96.454.3033.1 |
| EAN        | 4015573920736 |
| Order Unit | 5 Piece(s)    |

## Certificates / Approvals



## Technical data

### General

|                                          |       |
|------------------------------------------|-------|
| Rated current                            | 20 A  |
| Rated voltage                            | 400 V |
| Rated impulse voltage                    | 4 kV  |
| Pollution degree                         | 3     |
| Mechanical coding                        | Yes   |
| Interlockable                            | Yes   |
| Color of coding/ contact carrier         | Black |
| Marking of poles                         |       |
| Color of housing inclusive strain relief | Black |

### Model

|                                 |                                     |
|---------------------------------|-------------------------------------|
| Number of poles                 | 5                                   |
| Nominal cross section conductor | 4 mm <sup>2</sup>                   |
| Degree of protection (IP)       | IP66/IP68                           |
| Wire strip length               | 9 mm                                |
| sheath strip length             | 35 mm                               |
| Preparation of conductor ends   | Ultrasonically compressed wire ends |
| Cable type                      | H07RN-F                             |

|                  |                   |
|------------------|-------------------|
| Cable colour     | Black             |
| Cable diameter   | 17 mm             |
| Version of cable | Female - free end |

#### Material

|                                              |               |
|----------------------------------------------|---------------|
| Surface finish                               | Silver-plated |
| Halogen free                                 | No            |
| Continuous temperature of cable              | 60 °C         |
| Insulation components continuous temperature | 100 °C        |

#### Dimensions

|              |     |
|--------------|-----|
| Total length | 3 m |
|--------------|-----|

#### Technical drawing

