



Product data sheet

Item No. 96.452.3034.6

Cable assembly RST20I5KS-S 15 30TB04

Connection cable, male - free end, length 3m, RST20i5, 5 pole, mains 250V/dimming, 16A, cable type H07RN-F, cross section $1,5\text{mm}^2$, color of coding: turquoise



Item No.	96.452.3034.6
EAN	4015573941717
Order Unit	10 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	16 A
Rated voltage	250 V
Rated voltage 2	50 V
Rated impulse voltage	4 kV
Pollution degree	3
Mechanical coding	Yes
Interlockable	Yes
Color of coding/ contact carrier	Turquoise
Marking of poles	
Color of housing inclusive strain relief	Black

Model

Number of poles	5
Nominal cross section conductor	1.5 mm ²
Degree of protection (IP)	IP66/IP68
Wire strip length	9 mm
sheath strip length	35 mm
Preparation of conductor ends	Ultrasonically compressed wire ends





Cable type	H07RN-F
Cable colour	Black
Cable diameter	12.2 mm
Version of cable	Male - free end

Material

Surface finish	Silver-plated
Halogen free	No
Continuous temperature of cable	60 °C
Insulation components continous temperature	100 °C

Dimensions

- 1	Total length	3 m
	rotal length	S III

