

## Product data sheet

Item No. 96.834.1034.3

### Cable assembly RST25I3KS-S 40 10BG03

Connection cable, male - free end, length 1m, RST25i3, 3 pole, 250V/25A, cable type H07RN-F, cross section 4,0 mm<sup>2</sup>, color of coding: concrete gray



|            |               |
|------------|---------------|
| Item No.   | 96.834.1034.3 |
| EAN        | 4015573896475 |
| Order Unit | 30 Piece(s)   |

## Certificates / Approvals



## Technical data

### General

|                                          |               |
|------------------------------------------|---------------|
| Rated current                            | 25 A          |
| Rated voltage                            | 250 V         |
| Rated impulse voltage                    | 4 kV          |
| Pollution degree                         | 3             |
| Mechanical coding                        | Yes           |
| Interlockable                            | Yes           |
| Color of coding/ contact carrier         | Concrete gray |
| Marking of poles                         |               |
| Color of housing inclusive strain relief | Black         |

### Model

|                                 |                                     |
|---------------------------------|-------------------------------------|
| Number of poles                 | 3                                   |
| Nominal cross section conductor | 4 mm <sup>2</sup>                   |
| Degree of protection (IP)       | IP66/IP68                           |
| Wire strip length               | 9 mm                                |
| sheath strip length             | 35 mm                               |
| Preparation of conductor ends   | Ultrasonically compressed wire ends |
| Cable type                      | H07RN-F                             |

|                  |                 |
|------------------|-----------------|
| Cable colour     | Black           |
| Cable diameter   | 13.4 mm         |
| Version of cable | Male - free end |

**Material**

|                                              |               |
|----------------------------------------------|---------------|
| Surface finish                               | Silver-plated |
| Halogen free                                 | No            |
| Continuous temperature of cable              | 60 °C         |
| Insulation components continuous temperature | 100 °C        |

**Dimensions**

|              |     |
|--------------|-----|
| Total length | 1 m |
|--------------|-----|

Technical drawing



