

## Product data sheet

Item No. 92.238.1560.1

### Cable assembly

geis® Extension cable female - male; length: 1,5m; type GST18I3; 3-pole; 250 V / 20 A; colour of coding: black with black strain-relief; cable: H05Z1Z1-F 3G2,5, colour: black



Item No.	92.238.1560.1
EAN	4015573733008
Order Unit	40 Piece(s)

### Certificates / Approvals



### Technical data

#### General

Rated current	20 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	2
Mechanical coding	Code 1
Interlockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	
Color of housing inclusive strain relief	Black

#### Model

Number of poles	3
Nominal cross section conductor	2.5 mm <sup>2</sup>
Degree of protection (IP)	IP40
Cable type	H05Z1Z1-F
Cable colour	Black
Cable diameter	10.2 mm
Version of cable	Female - male



Type of cord set	Connecting cable
Version cable end 1	GST18i3 socket
Version cable end 2	GST18i3 plug

**Material**

Surface finish	Tin-plated
Halogen free	Yes
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C

**Dimensions**

Total length	1.5 m
--------------	-------

**Technical drawing**

.F	Farbe colour	Codierung *X* Buchse female	Codierung *Y* Stecker male	Kabelfarbe cable colour
.1	schwarz black	[Diagram]	[Diagram]	schwarz black
.2	weiß white	[Diagram]	[Diagram]	weiß white
.3	grau grey	[Diagram]	[Diagram]	schwarz black
.5	rot red	[Diagram]	[Diagram]	schwarz black

**Kabeltype/cable-type** H05Z1Z1-F3G2,5 halogenfrei/halogen-free  
**Farbe/colour:** siehe Tabelle/see table

**Typ/type:** GST18i3K1BS 25H.

Teile-Nr. part-no.	L	Beispiel (Farbe: schwarz) exempl (colour: black)	Typ type
92.238.XX60.F	XX in dm-Schritten	92.238.1060.1 = 10dm/L= 1000mm	GST18i3K1BS 25H 10SW
U2.238.XX60.F	XX in m-Schritten	U2.238.1260.1 = 12 m/L=12000mm	GST18i3K1BS 25H X12SW
92.238.XX80.F	XX in dm-Schritten	92.238.1080.1 = 10dm/L= 1000mm	

80.F = spezielle Verpackung und Etikettierung nach A 1960.000  
special packaging and label according to A 1960.000

Freiwillig nach 030 - Drawing, as manual modifications allowed First Use: [ ] ( ) [ ] [ ]

Material/Material	Zu/Die Tag/Date	Name	Zeichnung Nr./Drawing No.
[ ]	[ ]	[ ]	92.238.0260.1 01K b

PRE-ASSEMBLED CABLE KONFEKT LEITUNG

Buchse/female - Stecker/male Crimpversion K1 halogen-free

③ 250V AC 20A 2,5mm