

## Product data sheet

Item No. 96.223.6092.8

### Cable assembly RST20i2K1BS325OL 60KG06

Extension cable, female - male, length 6m, RST20i2, 2 pole, 50V, 20A, cable type Ölflex classic 100, cross section 2,5 mm<sup>2</sup>, color of coding: pebble gray



|            |               |
|------------|---------------|
| Item No.   | 96.223.6092.8 |
| EAN        | 4015573966741 |
| Order Unit | 15 Piece(s)   |

## Certificates / Approvals



## Technical data

### General

|                                          |             |
|------------------------------------------|-------------|
| Rated current                            | 20 A        |
| Rated voltage                            | 24 V        |
| Rated impulse voltage                    | 4 kV        |
| Pollution degree                         | 3           |
| Mechanical coding                        | Yes         |
| Interlockable                            | Yes         |
| Color of coding/ contact carrier         | Pebble gray |
| Marking of poles                         |             |
| Color of housing inclusive strain relief | Black       |

### Model

|                                 |                     |
|---------------------------------|---------------------|
| Number of poles                 | 2                   |
| Nominal cross section conductor | 2.5 mm <sup>2</sup> |
| Degree of protection (IP)       | IP66/IP68           |
| Cable type                      | Ölflex Classic 100  |
| Cable colour                    | Grey                |
| Cable diameter                  | 8.9 mm              |
| Version of cable                | Female - male       |

## Material

|                                              |               |
|----------------------------------------------|---------------|
| Surface finish                               | Silver-plated |
| Halogen free                                 | No            |
| Continuous temperature of cable              | 70 °C         |
| Insulation components continuous temperature | 100 °C        |

## Dimensions

|              |     |
|--------------|-----|
| Total length | 6 m |
|--------------|-----|

## Technical drawing

