

Product data sheet

Item No. 96.854.4004.3

Cable assembly RST25I5KS-S 40P 40BG03

Connection cable, male - free end, length 4m, RST25i5, 5 pole, 250V/25A, cable type H05VV, cross section 4,0 mm², color of coding: concrete gray



Item No.	96.854.4004.3
EAN	4015573901988
Order Unit	5 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	25 A
Rated voltage	400 V
Rated impulse voltage	4 kV
Pollution degree	3
Mechanical coding	Yes
Interlockable	Yes
Color of coding/ contact carrier	Concrete gray
Marking of poles	
Color of housing inclusive strain relief	Black

Model

Number of poles	5
Nominal cross section conductor	4 mm ²
Degree of protection (IP)	IP66/IP68
Wire strip length	9 mm
sheath strip length	35 mm
Preparation of conductor ends	Ultrasonically compressed wire ends
Cable type	H05VV-F

Cable colour	Black
Cable diameter	14.3 mm
Version of cable	Male - free end

Material

Surface finish	Silver-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C

Dimensions

Total length	4 m
--------------	-----

Technical drawing

