

Product data sheet

Item No. 96.834.4004.3

Cable assembly RST25I3KS-S 40P 40BG03

Connection cable, male - free end, length 4m, RST25i3, 3 pole, 250V/25A, cable type H05VV, cross section 4,0 mm², color of coding: concrete gray



Item No.	96.834.4004.3
EAN	4015573896321
Order Unit	8 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	25 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	3
Mechanical coding	Yes
Interlockable	Yes
Color of coding/ contact carrier	Concrete gray
Marking of poles	
Color of housing inclusive strain relief	Black

Model

Number of poles	3
Nominal cross section conductor	4 mm ²
Degree of protection (IP)	IP66/IP68
Wire strip length	9 mm
sheath strip length	35 mm
Preparation of conductor ends	Ultrasonically compressed wire ends
Cable type	H05VV-F

Cable colour	Black
Cable diameter	11.4 mm
Version of cable	Male - free end

Material

Surface finish	Silver-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C

Dimensions

Total length	4 m
--------------	-----

Technical drawing

1	2	3	A												
A B C D E F	Gesamtlänge/totale length L ± 3% cable type Kabeltype H05VV-F 3G4,0 color: concrete grey, similar to RAL 7023 Farbe: betongrau, ähnl. RAL 7023	1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 M1 M2 M3 L G i 11.1 12.1 1.1	These dimensions will be especially checked at delivery Only inspection dimensions With /E marked dimensions are only valid for internal use These Maße werden bei Abnahme besonders geprüft Ausschließlich Prüfmäße Mit /E gekennzeichnete Maße sind nur für interne Zwecke gültig												
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 15%;">Teile-Nr. part-no.</td> <td style="width: 15%;">L</td> <td style="width: 35%;">Beispiel (Farbe: betongrau) exampel (colour: concrete grey)</td> <td style="width: 35%;">Typ type</td> </tr> <tr> <td>96.834.XX04.3</td> <td>XX in dm-Schritten</td> <td>96.834.1004.3 = 10dm/L= 1000mm</td> <td>RST25I3KS-S 40P 10BG03</td> </tr> <tr> <td>U6.834.XX04.3</td> <td>XX in m-Schritten</td> <td>U6.834.1204.3 = 12 m/L=12000mm</td> <td>RST25I3KS-S 40P X12BG03</td> </tr> </table>				Teile-Nr. part-no.	L	Beispiel (Farbe: betongrau) exampel (colour: concrete grey)	Typ type	96.834.XX04.3	XX in dm-Schritten	96.834.1004.3 = 10dm/L= 1000mm	RST25I3KS-S 40P 10BG03	U6.834.XX04.3	XX in m-Schritten	U6.834.1204.3 = 12 m/L=12000mm	RST25I3KS-S 40P X12BG03
Teile-Nr. part-no.	L	Beispiel (Farbe: betongrau) exampel (colour: concrete grey)	Typ type												
96.834.XX04.3	XX in dm-Schritten	96.834.1004.3 = 10dm/L= 1000mm	RST25I3KS-S 40P 10BG03												
U6.834.XX04.3	XX in m-Schritten	U6.834.1204.3 = 12 m/L=12000mm	RST25I3KS-S 40P X12BG03												
Tolerierung nach DIN 7167/Tolerance system acc. to DIN 7167. (This DIN-standard describes the envelope principle. According to the envelope principle the deviations of form and parallelism are limited by the size tolerances). ja/yes ☒ Stoffverbots- und Deklarationsliste nach UU-TOM-05/03 ist einzuhalten. Conformity with Wieland document UU-TOM-05/03 (List of prohibited / deklarable hazardous substances) to be declared!															
Freitoleranz nach General tolerance		CAD - Zeichnung, keine manuellen Änderungen CAD - drawing, no manual modifications allowed	1. Verwendung: - First Use:												
Blatt: 1 von 1 Sheet: 1 of 1		Zeichnung Nr./Drawing No. Index 96.834.1004.3 01K a													
Werkstoff/Material		2006 Tag/Date Name gezeichnet drawn 02.02. Kneitz geprüft checked - - Normgepr. Stand, check - -	Maße in mm/Dimensions are in mm												
Vol. mm³ Off./Surf. mm² Ersatz für/Replacement for: -		Type Benennung/Title KONFEKT_LEITUNG ready made cables Schraubanschluss ohne Drahtschutz/screw-connection without wire protection													
13.02.2008/ Index Datum / Blatt Date / Sheet Änderung/Revision		wieland Elektrische Verbindungen													

