

Product data sheet

Item No. 96.454.3034.6

Cable assembly RST20I5KS-S 40 30TB04

Connection cable, male - free end, length 3m, RST20i5, 5 pole, mains 250V/dimming, 20A, cable type H07RN-F, cross section 4,0 mm², color of coding: turquoise



Item No.	96.454.3034.6
EAN	4015573943216
Order Unit	5 Piece(s)

Certificates / Approvals

Technical data

General

Rated current	20 A
Rated voltage	250 V
Rated voltage 2	50 V
Rated impulse voltage	4 kV
Pollution degree	3
Mechanical coding	Yes
Interlockable	Yes
Color of coding/ contact carrier	Turquoise
Marking of poles	
Color of housing inclusive strain relief	Black

Model

Number of poles	5
Nominal cross section conductor	4 mm ²
Degree of protection (IP)	IP66/IP68
Wire strip length	9 mm
sheath strip length	35 mm
Preparation of conductor ends	Ultrasonically compressed wire ends
Cable type	H07RN-F
Cable colour	Black

Cable diameter	17 mm
Version of cable	Male - free end

Material

Surface finish	Silver-plated
Halogen free	No
Continuous temperature of cable	60 °C
Insulation components continuous temperature	100 °C

Dimensions

Total length	3 m
--------------	-----

Technical drawing

