

Product data sheet

Item No. 96.834.2000.3

Cable assembly RST25I3KSBS 40P 20BG03

Extension cable, female - male, length 2m, RST25i3, 3 pole, 250V/25A, cable type H05VV, cross section 4,0 mm², color of coding: concrete gray



Item No.	96.834.2000.3
EAN	4015573896147
Order Unit	15 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	25 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	3
Mechanical coding	Yes
Interlockable	Yes
Color of coding/ contact carrier	Concrete gray
Marking of poles	
Color of housing inclusive strain relief	Black

Model

Number of poles	3
Nominal cross section conductor	4 mm ²
Degree of protection (IP)	IP66/IP68
Cable type	H05VV-F
Cable colour	Black
Cable diameter	11.4 mm
Version of cable	Female - male

Material

Surface finish	Silver-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C

Dimensions

Total length	2 m
--------------	-----

Technical drawing

1	2	3	A
These dimensions will be especially checked at delivery Only inspection dimensions With /± marked dimensions are only valid for internal use Diese Maße werden bei Abnahme besonders geprüft Ausschließlich Prüfmäße Mit /± gekennzeichnete Maße sind nur für interne Zwecke gültig	cable type: Kabeltype: H05VV-F 3G4,0 color: concrete grey, similar to RAL 7023 Farbe: betongrau, ähnl. RAL 7023 color: concrete grey, similar to RAL 7023 Farbe: betongrau, ähnl. RAL 7023 Gesamtlänge/totale length L ± 3%		1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 M1 M2 M3 L G i 11.1 12.1 1.1
Teile-Nr. / part-no. L Beispiel (Farbe: betongrau) / example (colour: concrete grey) Typ / type			
96.834.XX00.3		XX in dm-Schritten	96.834.1000.3 = 10dm/L= 1000mm
U6.834.XX00.3		XX in m-Schritten	U6.834.1200.3 = 12 m/L=12000mm
Tolerierung nach DIN 7167/Tolerance system acc. to DIN 7167. (This DIN-standard describes the envelope principle. According to the envelope principle the deviations of form and parallelism are limited by the size tolerances). ja/yes ☒ Stoffverbots- und Deklarationsliste nach UU-TOM-05/03 ist einzuhalten. Conformity with Wieland document UU-TOM-05/03 (list of prohibited / declarable hazardous substances) to be declared!			
Freitoleranz nach General tolerance		CAD - Zeichnung, keine manuellen Änderungen CAD - drawing, no manual modifications allowed	1. Verwendung: - First Use: -
Blatt: 1 von 1 Sheet: 1 of 1			
Werkstoff/Material 2006 Tag/Date Name gezeichnet 02.02. Kneitz geprüft - - - Normgepr. Stand, check - - -		Zeichnung Nr./Drawing No. 96.834.1000.3 01K Index a	
Maßstab/Scale		Maße in mm/Dimensions are in mm	
Vol. mm² Offl./Surf. mm²		Ersatz für/Replacement for: -	
1:1		96.834.1000.3 01K	
a 13.02.2008/ Index Datum / Blatt Date / Sheet		KONFEKT_LEITUNG ready made cables Schraubanschluss ohne Drahtschutz/screw-connection with cord grip	
Änderung/Revision		Benennung/Title	

