

EASY SPOOL INSTALLER PACK COMPRISING 31XL2-ZH (50 METRE REEL)

CATALOG NUMBER

1244-021269



nVent RAYCHEM contractor packs comprise a fixed length of heating cable supplied in an easy-to-use and carry spool box. The spool allows the installer to feed out the required length easily, reducing installation time and effort.

FEATURES

Unparalleled safety, low smoke zero halogen construction: up to 90% less smoke emissions and improved self-extinguishing properties

Zero halogen: IEC60754-1 tested and compliant

Improved self-extinguishing properties under the IEC62395 flammability test

Energy efficient: self-regulating cable, major savings when used with proportional ambient sensing controller (PASC), no cable overheating possible

Self-regulating technology: cut-to-length on site to mitigate any design variations

Quick and easy installation with the RayClick fast connection system

PRODUCT ATTRIBUTES

Article Number: XL-Trace-InstallerPack-31XL-50m

Heating Cable Technology: Self-Regulating

Supply Voltage: 220 – 240 V

Nominal Voltage: 220 V; 230 V; 240 V

Length: 50 m

Nominal Power Output @ 5°C, 230V: 31 W/m

Max Continuous Exposure Temperature, Power On: 85 °C

Max Intermittent Exposure Temperature, Power On: 90 °C

Max Cumulative Hours for Intermittent Exposure: 800 h

Outer Jacket Material: Low Smoke Zero Halogen

Color: Purple

Ground Path Type: Braid

Min Installation Temperature: -40 °C

Conductor Material: Nickel-Plated Copper

Conductor Quantity: 2

Nominal Cable Weight: 135 g/m

Nominal Height: 6.8 mm

Nominal Width: 13.8 mm

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

Noord-Amerika

Tel. +1.800.545.6258

Fax +1.800.527.5703

thermal.info@nvent.com

Europa, het Midden-Oosten, Afrika

Tel. + 32.16.213.51 1

Fax + 32.16.213.60 4

thermal.info@nvent.com

Van Azië en de Stille Oceaan

Tel. +86.21.2412.1688

Fax +86.21.5426.3167

cn.thermal.info@nvent.com

Latijns-Amerika

Tel. +1.713.868.4800

Fax +1.713.868.2333

thermal.info@nvent.com



Onze krachtige portefeuille van merken:
nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER

© nVent 2022. Alle nVent tekens en emblemen worden bezeten of door de nVent Diensten GmbH of zijn filialen vergunning gegeven. Alle andere handelsmerken zijn het bezit van hun respectieve eigenaars.

nVent reserves het recht specificaties zonder bericht te veranderen.