

## T2RED SELF-REGULATING HEATING CABLE, 230 V, 5-15 W/M

### CATALOG NUMBER

**948739-000**



nVent RAYCHEM T2Red and Reflecta combines a self-regulating floor heating cable with perfect heat spreading and insulation boards. Suitable for new build and renovation, they can be applied under any type of floor surface without risk of overheating. Ideal for wooden and engineered wooden floors but also for natural stone and ceramic tiles.

### FEATURES

Energy efficient and self regulating: automatically adjusts heat output, more heat near windows, less heat under furnishings

Maximum comfort with T2Reflecta insulation board: heat spreads perfectly over the entire room

Simple, fast installation: cut-to-length, no cold leads, If combined with Reflecta then pre-grooves serve as cable fixing tool and guarantee perfect cable distance of 100-200 or 300mm spacing, suitable for all sub-floors and floor coverings, meter markings, user-friendly connections kits

Safe and efficient operation: fast heat up, uniform temperatures across the room, flexible power output from 35-100W/m<sup>2</sup>, closer loops for higher output and wider loops for lower output, no overheating

Reliable during long life: 12 to 20 year total care warranty available, no maintenance required

Advanced control options available

### PRODUCT ATTRIBUTES

Article Number: T2-RED

Heating Cable Technology: Self-Regulating

Nominal Voltage: 230 V

Power Output: 5 – 15 W/m

Power Output, Typical: 80 – 125 W/m<sup>2</sup>

Outer Jacket Material: Fluoropolymer

Color: Red

Ground Path Type: Braid

Min Installation Temperature: 5 °C

Conductor Material: Nickel-Plated Copper

Conductor Quantity: 2

Nominal Width: 8.5 mm

Nominal Height: 5.8 mm

Nominal Cable Weight: 68 g/m

Max Continuous Exposure Temperature, Power Off: 65 °C

Max Continuous Exposure Temperature, Power On: 65 °C

Min Bending Radius: 35 mm

Max Circuit Length: 100 m

Circuit Breaker: Type C/10Amp

## WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.nvent.com](http://www.nvent.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

### Noord-Amerika

Tel. +1.800.545.6258

Fax +1.800.527.5703

[thermal.info@nvent.com](mailto:thermal.info@nvent.com)

### Europa, het Midden-Oosten, Afrika

Tel. + 32.16.213.51 1

Fax + 32.16.213.60 4

[thermal.info@nvent.com](mailto:thermal.info@nvent.com)

### Van Azië en de Stille Oceaan

Tel. +86.21.2412.1688

Fax +86.21.5426.3167

[cn.thermal.info@nvent.com](mailto:cn.thermal.info@nvent.com)

### Latijns-Amerika

Tel. +1.713.868.4800

Fax +1.713.868.2333

[thermal.info@nvent.com](mailto:thermal.info@nvent.com)



Onze krachtige portefeuille van merken:  
**nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER**

© nVent 2022. Alle nVent tekens en emblemen worden bezeten of door de nVent Diensten GmbH of zijn filialen vergunning gegeven. Alle andere handelsmerken zijn het bezit van hun respectieve eigenaars.

nVent reserves het recht specificaties zonder bericht te veranderen.