



## FLANGED DROP-IN ANCHOR, M8 HOLE

### CATALOG NUMBER

**LAM830**



### CERTIFICATIONS



### FEATURES

Internal thread provides easy removal and serviceability

Installs flush for standard embedment

Suitable for redundant non-structural systems on cracked and non-cracked concrete

Fire resistance class R30-R120 for design of anchorages under exposure to fire

Lip makes the flush installation easier by helping achieve consistent anchor depth and easy threaded rod alignment

### PRODUCT ATTRIBUTES

Article Number: 574410

Material: Steel


Finish: Electrogalvanized

Hole Size: M8

Length: 30 mm

Drill Bit Diameter: 10 mm

## DIAGRAMS



**Characteristic Axial Loads from ETA 14-0135**

| Part Number | Cracked Concrete C20/25 | Non-Cracked Concrete C20/25 | Standard Embedment Depth |
|-------------|-------------------------|-----------------------------|--------------------------|
| LAM625      | -                       | 2.44 kN                     | 25 mm                    |
| LAM830      | -                       | 3.21 kN                     | 30 mm                    |
| LAM1040     | -                       | 4.23 kN                     | 40 mm                    |
| LAM1250     | -                       | 5.92 kN                     | 50 mm                    |

**Characteristic Axial Loads from ETA 14-0068 - for redundant non-structural systems**

| Part Number | Cracked Concrete C20/25 | Non-Cracked Concrete C20/25 | Standard Embedment Depth |
|-------------|-------------------------|-----------------------------|--------------------------|
| LAM625      | 0.80 kN                 | 0.80 kN                     | 25 mm                    |
| LAM830      | 1.20 kN                 | 1.20 kN                     | 30 mm                    |
| LAM1040     | 1.70 kN                 | 1.70 kN                     | 40 mm                    |
| LAM1250     | 2.60 kN                 | 2.60 kN                     | 50 mm                    |

## WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.nvent.com](http://www.nvent.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

**Noord-Amerika**

+1.800.753.9221

Optie 1 - de Zorg van de Klant

Optie 2 - Technische Steun

**Europa**

Nederland:

+31 800-0200135

Frankrijk:

+33 800 901 793

**Europa**

Duitsland:

800 1890272

Andere Landen:

+31 13 5835404

**APAC**

Shanghai:

+ 86 21 2412 1618/19

Sydney:

+61 2 9751 8500



Onze krachtige portefeuille van merken:  
**nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER**

© nVent 2022. Alle nVent tekens en emblemen worden bezeten of door de nVent Diensten GmbH of zijn filialen vergunning gegeven. Alle andere handelsmerken zijn het bezit van hun respectieve eigenaars.

nVent reserves het recht specificaties zonder bericht te veranderen.