



H-TI/T ROD TO FLANGE CLIP, M6 HOLE, THREADED, 0.08"–0.12" FLANGE

CATALOG NUMBER

M6TI4



CERTIFICATIONS



FEATURES

Suspends threaded rod from beam flanges

Threaded rod hanger can swivel to provide a vertical dropdown

Requires only a hammer to install

PRODUCT ATTRIBUTES

Article Number: 174810

Material: Spring Steel

Finish: nVent CADDY Armour


Hole Size: M6

Hole Type: Threaded

Flange Thickness: 2 – 3 mm

Static Load: 700 N

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

Noord-Amerika

+1.800.753.9221
Optie 1 - de Zorg van de Klant
Optie 2 - Technische Steun

Europa

Nederland:
+31 800-0200135
Frankrijk:
+33 800 901 793

Europa

Duitsland:
800 1890272
Andere Landen:
+31 13 5835404

APAC

Shanghai:
+ 86 21 2412 1618/19
Sydney:
+61 2 9751 8500



Onze krachtige portefeuille van merken:
nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER