

FBS FLAT BUSBAR SUPPORT

CATALOG NUMBER

FBS400A



CERTIFICATIONS



FEATURES

Support for threaded busbars

Three phase with neutral circuit

Plastic positioning pin for bar location

Adjusts quickly to accommodate multiple busbar widths

Protection screen can be fixed using spacers

A ground can be mounted on either side

Halogeenvrij

PRODUCT ATTRIBUTES

Article Number: 551350

Material: Steel;Glass Fibre Reinforced Polyamide;Aluminum

Finish: Elektrolytisch gegalvaniseerd

Max Working Voltage, IEC (Ui): 1,000 VAC;1,500 VDC

Working Temperature: -40 to 130 °C

Typical Application Current Rating: 160 – 400 A

Complies With: IEC® 61439.1;IEC® 60695-2-11 (Glow Wire Test 960 °C)

Flammability Rating: UL® 94V-0

Busbar Width: 15 mm;20 mm;32 mm

Busbar Thickness: 5 mm

Height: 34 mm

Width: 465 mm

A: 450 mm

B: 300 mm

C: 18 mm


D: 26 mm

E: 50 mm

X: 6 x 8 mm

Unit Weight: 0.300 kg

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

Noord-Amerika
+1.800.753.9221
Option 1 – Customer Care
Option 2 – Technical Support

Europa
Netherlands:
+31 800-0200135
France:
+33 800 901 793

Europa
Germany:
800 1890272
Other Countries:
+31 13 5835404

APAC
Shanghai:
+ 86 21 2412 1618/19
Sydney:
+61 2 9751 8500



Our powerful portfolio of brands:
nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF
TRACER