


RTCBI INSULATED ROUND BRAID IN COIL, TINNED COPPER, 150 A NOMINAL CURRENT, 25 MM², 25 M

CATALOG NUMBER

RTCBI15-25



CERTIFICATIONS



FEATURES

Braids in coil are mainly used for power distribution or earthing applications

Non-magnetic material

Vertinde afwerking biedt een diefstalwerende verschijning

PRODUCT ATTRIBUTES

Article Number: 503420

Material: Copper;Polyvinylchloride

Finish: Vertind

Nominal Current: 150 A

Cross Section: 25 mm²

Number of Wires: 1,416

Wire Diameter: 0.15 mm

Length: 25 m

Diameter: 9.5 mm

Unit Weight: 0.250 kg
Insulation Thickness: 1 mm
Insulation Voltage: 450 V
Temperature: 70 °C Max
Flammability Rating: UL® 94V-0

ADDITIONAL PRODUCT DETAILS

Unit weight is per meter (3.28').

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

Noord-Amerika +1.800.753.9221 Option 1 – Customer Care Option 2 – Technical Support	Europa Netherlands: +31 800-0200135 France: +33 800 901 793	Europa Germany: 800 1890272 Other Countries: +31 13 5835404	APAC Shanghai: + 86 21 2412 1618/19 Sydney: +61 2 9751 8500
---	--	--	--