


VIERPOLIGE VERDEELBLOK MET GETAPTE RAIL, 160 A

CATALOG NUMBER

TRS-160A



CERTIFICATIONS



FEATURES

Easily fixes onto asymmetric DIN rail or mounts with screws

Bolts included for output connections

Transparent protection cover

Easy accessibility for wiring

Na uitpakken direct klaar voor gebruik, installatietijd en arbeid besparend

RoHS compliant

PRODUCT ATTRIBUTES

Article Number: 563160

Material: Copper;Glass Fibre Reinforced Polyamide;Plexiglass

Max Working Voltage, IEC (Ui): 630 V

Peak Short Circuit Current (I_{pk}): 34 kA

Short Term Withstand Current (I_{cw}) 1s: 13.2 kA

Line Side Number of Connections: 2

Load Side Number of Connections: 4

Hole Size: 8 mm

Thread Size: M6

Depth: 68 mm

Height: 150 mm

Width: 230 mm

Unit Weight: 1.150 kg


Flammability Rating: UL® 94V-0

Complies With: IEC® 60439.1; IEC® 61439.1; IEC® 60695-2-11 (Glow Wire Test 960 °C)

ADDITIONAL PRODUCT DETAILS

Line side and load side number of connections are per pole.

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

Noord-Amerika

+1.800.753.9221

Option 1 – Customer Care

Option 2 – Technical Support

Europa

Netherlands:

+31 800-0200135

France:

+33 800 901 793

Europa

Germany:

800 1890272

Other Countries:

+31 13 5835404

APAC

Shanghai:

+ 86 21 2412 1618/19

Sydney:

+61 2 9751 8500



Our powerful portfolio of brands:
nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF
TRACER