

# TTCE TUBULAR BRAID IN COIL, TINNED COPPER, 90 A NOMINAL CURRENT, 12 MM<sup>2</sup>, 50 M

## CATALOG NUMBER

**TTCE15**



The primary use of tubular braid is to provide sensitive cables with an EMC/EMI screen to shield them against electromagnetic, electrostatic and radio frequency interference. Optimum screening performance is obtained using copper wire braid that can also be used for earth continuity purposes.

## CERTIFICATIONS



## FEATURES

For screening connecting cables between equipment used in an electromagnetically disturbed environment

Supplied with draw wire

## PRODUCT ATTRIBUTES

Article Number: 510140

Finish: Vertind

Material: Koper

Nominal Current: 90 A

Cross Section: 12 mm<sup>2</sup>

Number of Wires: 334

Wire Diameter: 0.15 mm

Length: 50 m

Unit Weight: 0.120 kg

ADDITIONAL PRODUCT DETAILS

Unit weight is per meter (3.28').

| Coverage Efficiency |          |          |       |          |
|---------------------|----------|----------|-------|----------|
| Referentienummer    | Diameter |          |       |          |
|                     | Nom      | Coverage | Max   | Coverage |
| TTCE3               | 3 mm     | 100%     | 6 mm  | 90%      |
| TTCE5               | 5 mm     | 99%      | 10 mm | 92%      |
| TTCE8               | 8 mm     | 99%      | 16 mm | 95%      |
| TTCE8HL             | 8 mm     | 99%      | 16 mm | 95%      |
| TTCE10              | 10 mm    | 100%     | 20 mm | 92%      |
| TTCE15              | 15 mm    | 100%     | 25-mm | 94%      |
| TTCE20              | 20 mm    | 99%      | 40 mm | 87%      |
| TTCE25              | 25 mm    | 99%      | 50 mm | 92%      |
| TTCE30              | 30 mm    | 100%     | 60 mm | 90%      |
| TTCE35              | 35 mm    | 100%     | 70 mm | 94%      |

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.nvent.com](http://www.nvent.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

Noord-Amerika

+1.800.753.9221  
Option 1 – Customer Care  
Option 2 – Technical Support

Europa

Netherlands:  
+31 800-0200135  
France:  
+33 800 901 793

Europa

Germany:  
800 1890272  
Other Countries:  
+31 13 5835404

APAC

Shanghai:  
+ 86 21 2412 1618/19  
Sydney:  
+61 2 9751 8500



Our powerful portfolio of brands:  
nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF  
TRACER