


UNIVERSAL BUSBAR SUPPORT WITH NEUTRAL CIRCUIT, HIGH AMPACITY, 1 BUSBARS PER PHASE, 160 MM BUSBAR WIDTH

CATALOG NUMBER

UBS1-10TN-160



CERTIFICATIONS



FEATURES

Universal fixing system

Installs quickly and easily

Extremely robust construction

Screws are made from non-magnetic stainless steel

Halogen free insulators

PRODUCT ATTRIBUTES

Article Number: 561500

Material: Steel;Glass Fibre Reinforced Polyamide

Max Working Voltage, IEC (Ui): 1,000 VAC;1,500 VDC

Working Temperature: -40 to 130 °C


Complies With: IEC® 60439.1;IEC® 61439.1;IEC® 60695-2-11 (Glow Wire Test 960 °C)

Flammability Rating: UL® 94V-0

Typical Application Current Rating: 3,500 A

Busbars per Phase: 1
Busbar Width: 160 mm
Busbar Thickness: 10 mm
Width: 300 mm
A: 70 mm
Unit Weight: 2.300 kg

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

Noord-Amerika +1.800.753.9221 Option 1 – Customer Care Option 2 – Technical Support	Europa Netherlands: +31 800-0200135 France: +33 800 901 793	Europa Germany: 800 1890272 Other Countries: +31 13 5835404	APAC Shanghai: + 86 21 2412 1618/19 Sydney: +61 2 9751 8500
---	--	--	--