

# ADJUSTABLE FLAT BUSBAR SUPPORT KIT

#### **CATALOG NUMBER**

## AFBS-B600



## **CERTIFICATIONS**





#### **FEATURES**

Kit includes rail, insulators and mountable extension arms

Adjustable distances between phases

Adjusts quickly to accommodate multiple busbar thicknesses

Hoge weerstand tegen kortsluitingskrachten

Provides excellent electrical protection for equipment

Three phase with neutral circuit

Halogeenvrij

RoHS compliant

### **PRODUCT ATTRIBUTES**

Article Number: 504971

Material: Steel; Aluminum; Glass Fibre Reinforced Polyamide

Max Working Voltage, IEC (Ui): 1,000 VAC;1,500 VDC

Working Temperature: -40 to 130 °C

Complies With: IEC® 60439.1;IEC® 61439.1;IEC® 60695-2-11 (Glow Wire Test 960 °C)

Flammability Rating: UL® 94V-0

Busbar Width: 30 - 80 mm

Busbar Thickness: 5 - 10 mm

Height: 70 mm

Width: 549 - 749 mm

A: 507 mm


B: 61 - 176 mm

C: 525 - 725 mm

Screw Diameter: M8

Unit Weight: 2.200 kg

#### **DIAGRAMS**





#### **WARNING**

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

#### Noord-Amerika

+1.800.753.9221

Option 1 – Customer Care

Option 2 - Technical Support

Europa

Netherlands:

+31 800-0200135

France:

+33 800 901 793

Europa

Germany:

800 1890272

Other Countries:

+31 13 5835404

**APAC** 

Shanghai:

+ 86 21 2412 1618/19

Sydney:

+61 2 9751 8500



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN RAYCHEM SCHROFF

nVent.com
TRACER