

BUSBAR VOOR AARDING EN N-GELEIDER, MESSING, 166 AANSL.

CATALOG NUMBER

EB168



nVent ERIFLEX Connecting, Earthing and Neutral Busbars are used to connect several earthing conductors within a panel and can be used in a variety of different applications including switchgear and control equipment, electrical equipment, for wind and solar power generation and in data centers.

CERTIFICATIONS



FEATURES

Use to connect several earthing conductors

Chamfered holes allow for easy connections

Rigid bar

RoHS compliant

PRODUCT ATTRIBUTES

Article Number: 568630

Material: Messing

Number of Connections: 166

Conductor Size, IEC: (166) 1.5 - 4 mm² Stranded

Ferrule Conductor Size, IEC: (166) 0.75 - 4 mm²

Conductor Size, UL: (166) #16 - #10 Solid;(166) #10 Stranded

Depth: 8 mm

Height: 8 mm

Width: 1,000 mm

A: 6 mm
Unit Weight: 0.454 kg
Complies With: IEC® 61439.1

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

Noord-Amerika +1.800.753.9221 Option 1 – Customer Care Option 2 – Technical Support	Europa Netherlands: +31 800-0200135 France: +33 800 901 793	Europa Germany: 800 1890272 Other Countries: +31 13 5835404	APAC Shanghai: + 86 21 2412 1618/19 Sydney: +61 2 9751 8500
---	--	--	--