

VERMOGENAANSLUITBLOK TUNNEL-NAAR-TUNNEL, 350 A

CATALOG NUMBER

SBTT-350



CERTIFICATIONS



FEATURES

Tinned copper block allows for copper or aluminum conductor connections

Accessible tunnels allow for easy connection of wire

Design allows for visual inspection of conductor and confirmation of connection

Adjustable transparent cover

Modulaire blokken met klikbevestiging voor het bouwen van meerpolige voedingsblokken

Easily clips onto DIN rail or mounts to panel with screws

SBLEC Power Terminals Fixing Accessory required for direct panel mount

RoHS compliant

Halogeenvrij

PRODUCT ATTRIBUTES

Article Number: 561143

Material: Copper;Thermoplastic

Finish: Vertind

Max Current Rating, IEC: 500 A


Max Current Rating, UL/CSA: 310 A
Short Term Withstand Current (Icw) 1s: 22.2 kA
Peak Short Circuit Current (Ipk): 43 kA
Short Circuit Current Rating (SCCR): 100 kA
Max Working Voltage, IEC (Ui): 1,000 VAC;1,500 VDC
Max Working Voltage, UL (Vin): 1,000 VAC/DC
Number of Tunnel Connections: 2
Tunnel Connection Compact Stranded Wire Size: (2) 35 – 185 mm²
Tunnel Connection Wire Size - Ferrule: (2) 35 – 150 mm²
Tunnel Connection Wire Size: (2) #2 – 350 kcmil
Depth: 66 mm
Height: 205.70 mm
Width: 52.300 mm
A: 108 mm
Unit Weight: 0.330 kg
Certification Details: UL® 1059
Flammability Rating: UL® 94V-1
Complies With: IEC® 60947-7-1

ADDITIONAL PRODUCT DETAILS

Power terminal connections are interchangeable and can be used as line side or load side connections.

Design Guideline for Distribution Blocks, Power Blocks and Power Terminals										
Derating according to Ambient* Temperature (°C) to maintain working temperature of 85°C										
Ambient Temperature (°C)	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°
Derating Coefficient (d)	1	1	1	0.94	0.88	0.82	0.75	0.67	0.58	0.47
*environment around the terminal blocks inside the enclosure										

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

Noord-Amerika

+1.800.753.9221
Option 1 – Customer Care
Option 2 – Technical Support

Europa

Netherlands:
+31 800-0200135
France:
+33 800 901 793

Europa

Germany:
800 1890272
Other Countries:
+31 13 5835404

APAC

Shanghai:
+ 86 21 2412 1618/19
Sydney:
+61 2 9751 8500



Our powerful portfolio of brands:
nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF
TRACER