

AARDINGS-EN EQUIPOTENTIALAAL LITZE, 10 MM², 300 MM

CATALOG NUMBER

BJ10-300S



CERTIFICATIONS



FEATURES

Na uitpakken direct klaar voor gebruik, installatietijd en arbeid besparend

Allows for bending very close to the contact area

RoHS compliant

PRODUCT ATTRIBUTES

Article Number: 556920

Finish: Vertind

Material: Koper

Working Temperature: 105 °C Max

Ampacity: 75 A

Cross Section: 10 mm²

Length: 300 mm

Wire Diameter: 0.15 mm

Hole Size: 6.50 mm

Unit Weight: 0.033 kg

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

Noord-Amerika +1.800.753.9221 Option 1 – Customer Care Option 2 – Technical Support	Europa Netherlands: +31 800-0200135 France: +33 800 901 793	Europa Germany: 800 1890272 Other Countries: +31 13 5835404	APAC Shanghai: + 86 21 2412 1618/19 Sydney: +61 2 9751 8500
---	--	--	--