

CABS MODULE KIT WITH NEUTRAL, 1–3 BUSBARS PER PHASE, 30–120 MM BUSBAR WIDTH, 10 MM BUSBAR THICKNESS

CATALOG NUMBER

CABS3-10TN-MOD



CERTIFICATIONS



FEATURES

Modules provide flexibility to select distance between phases and supports

Installs quickly and easily

Halogen free insulators

RoHS compliant

PRODUCT ATTRIBUTES

Article Number: 549360

Material: Steel;Glass Fibre Reinforced Polyamide

Finish: Elektrolytisch gegalvaniseerd

Typical Application Current Rating: 400 – 4,500 A

Max Working Voltage, IEC (Ui): 1,000 VAC;1,500 VDC

Working Temperature: -40 to 130 °C

Complies With: IEC® 60439.1;IEC® 61439.1;IEC® 60695-2-11 (Glow Wire Test 960 °C)

Flammability Rating: UL® 94V-0

Busbars per Phase: 1 – 3
Busbar Width: 30 – 120 mm
Busbar Thickness: 10 mm
Depth: 39 mm
Width: 100 mm
Unit Weight: 0.580 kg

ADDITIONAL PRODUCT DETAILS

CABS modules must be installed on CABS-APP Aluminium Profile.

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

Noord-Amerika +1.800.753.9221 Option 1 – Customer Care Option 2 – Technical Support	Europa Netherlands: +31 800-0200135 France: +33 800 901 793	Europa Germany: 800 1890272 Other Countries: +31 13 5835404	APAC Shanghai: + 86 21 2412 1618/19 Sydney: +61 2 9751 8500
---	--	--	--