

BUSBAR VOOR AARDING EN N-GELEIDER, MESSING, 12 AANSL., GROTE HOEVEELH.

CATALOG NUMBER

EB12BLK200



nVent ERIFLEX Connecting, Earthing and Neutral Busbars are used to connect several earthing conductors within a panel and can be used in a variety of different applications including switchgear and control equipment, electrical equipment, for wind and solar power generation and in data centers.

CERTIFICATIONS



FEATURES

Use to connect several earthing conductors

Chamfered holes allow for easy connections

Rigid bar

RoHS compliant

PRODUCT ATTRIBUTES

Article Number: 568611

Material: Messing

Number of Connections: 12

Conductor Size, IEC: (2) 16 - 35 mm² Stranded;(10) 4 - 16 mm² Stranded

Ferrule Conductor Size, IEC: (2) 10 - 35 mm²;(10) 2.5 - 16 mm²


Conductor Size, UL: (2) #6 Solid;(10) #8 - #6 Solid;(2) #6 Stranded;(10) #8 - #6 Stranded

Max Current Rating: 250 A

Depth: 6 mm

Height: 13 mm
Width: 120 mm
A: 105 mm
B: 9 mm
Unit Weight: 0.068 kg
Complies With: IEC® 61439.1

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

Noord-Amerika +1.800.753.9221 Option 1 – Customer Care Option 2 – Technical Support	Europa Netherlands: +31 800-0200135 France: +33 800 901 793	Europa Germany: 800 1890272 Other Countries: +31 13 5835404	APAC Shanghai: + 86 21 2412 1618/19 Sydney: +61 2 9751 8500
---	--	--	--