

FLEXBUS ISOLEREND VERBAND FIB

CATALOG NUMBER

FLEXBANDAGE



CERTIFICATIONS



FEATURES

Intumescent wrap on the basis of butyl rubber with intumescent fire protection additives and glass-fabric reinforcement

To be used around Flexbus Conductors if the thickness of the penetration seal is < to 200mm

PRODUCT ATTRIBUTES

Article Number: 508152

Color: Red;Brown

Complies With: EN 13501-1;EN 1366-3

Length: 5,000 mm

Width: 150 mm

Unit Weight: 3.600 kg

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

Noord-Amerika

+1.800.753.9221

Option 1 – Customer Care

Option 2 – Technical Support

Europa

Netherlands:

+31 800-0200135

France:

+33 800 901 793

Europa

Germany:

800 1890272

Other Countries:

+31 13 5835404

APAC

Shanghai:

+ 86 21 2412 1618/19

Sydney:

+61 2 9751 8500



Our powerful portfolio of brands:
nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF
TRACER