


BUSBAR VOOR AARDING EN N-GELEIDER, VERNIKKELD . MESSING, 130 AANSL.

CATALOG NUMBER

EB130



CERTIFICATIONS



FEATURES

Use to connect several earthing conductors

Chamfered holes allow for easy connections

Main terminal clamp available for thicker conductors

Support bracket available for attaching busbar to DIN rail

Nickel plating is corrosion resistant

Rigid bar

Op de gewenste lengte te snijden

Snelle en eenvoudige installatie

RoHS compliant

PRODUCT ATTRIBUTES

Article Number: 568673

Material: Messing

Finish: Met nikkel bekleed

Number of Connections: 130

Conductor Size, IEC: 1.5 - 25 mm² Stranded

Max Current Rating: 125 A

Cross Section: 150 mm²

Depth: 15 mm

Height: 10 mm

Width: 1,000 mm

Hole Size: 6.50 mm

Thread Size: M5

A: 7 mm

Torque: 2 N-m

Unit Weight: 1.035 kg

Complies With: IEC® 60998-2-1

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

Noord-Amerika

+1.800.753.9221

Option 1 – Customer Care

Option 2 – Technical Support

Europa

Netherlands:

+31 800-0200135

France:

+33 800 901 793

Europa

Germany:

800 1890272

Other Countries:

+31 13 5835404

APAC

Shanghai:

+ 86 21 2412 1618/19

Sydney:

+61 2 9751 8500



Our powerful portfolio of brands:
nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF
TRACER