

FLEXBUS KNIPTANG

CATALOG NUMBER

FLEXSHEAR



FEATURES

Shear is used to cut the Flexbus Conductor over length

Favorable lever ratio and optimized cutting edge geometry require less effort

Adjustable bolted joint, self-retaining screw

Precision-ground, hardened blades

Allows for a clean, smooth cut without causing crushing or deformation

Guard provides added safety

High-grade special tool steel, forged, oil-hardened

PRODUCT ATTRIBUTES

Article Number: 508173

Material: Staal

Unit Weight: 0.324 kg

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

Noord-Amerika

+1.800.753.9221

Option 1 – Customer Care

Option 2 – Technical Support

Europa

Netherlands:

+31 800-0200135

France:

+33 800 901 793

Europa

Germany:

800 1890272

Other Countries:

+31 13 5835404

APAC

Shanghai:

+ 86 21 2412 1618/19

Sydney:

+61 2 9751 8500



Our powerful portfolio of brands:
nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF
TRACER