


PLATTE LITZE OP ROL VERTIND KOPER, 75 MM²

CATALOG NUMBER

FTCB15-75



CERTIFICATIONS



FEATURES

Braids in coil are mainly used for power distribution or earthing applications

Non-magnetic material

Vertinde afwerking biedt een diefstalwerende verschijning

PRODUCT ATTRIBUTES

Article Number: 557330

Material: Koper

Finish: Vertind

Wire Diameter: 0.15 mm

Nominal Current: 300 A

Cross Section: 75 mm²

Number of Wires: 4,256

Length: 25 m

Thickness: 4 mm

Width: 30 mm

Unit Weight: 0.750 kg

ADDITIONAL PRODUCT DETAILS

Unit weight is per meter (3.28').

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

Noord-Amerika

+1.800.753.9221
Option 1 – Customer Care
Option 2 – Technical Support

Europa

Netherlands:
+31 800-0200135
France:
+33 800 901 793

Europa

Germany:
800 1890272
Other Countries:
+31 13 5835404

APAC

Shanghai:
+ 86 21 2412 1618/19
Sydney:
+61 2 9751 8500



Our powerful portfolio of brands:
nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF
TRACER