

SBS ISOLATING SILICONE SLEEVE, 10 MM DIA, 100 M

CATALOG NUMBER

SBS-10



CERTIFICATIONS



FEATURES

Resistant to high temperature

Cost effective sleeve for insulation

High flexibility

Halogeenvrij

PRODUCT ATTRIBUTES

Article Number: 554030

Material: Fiberglass;Silicone

Insulation Voltage: 2.5 kV

Max Working Voltage, IEC (Ui): 690 VAC/DC

Max Working Voltage, UL (Vin): 690 VAC/DC

Working Temperature: -60 to 220 °C

Flammability Rating: UL® 1441 VW-1

Diameter: 10 mm

Length: 100 m

ADDITIONAL PRODUCT DETAILS

Unit weight is per meter (3.28').

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

Noord-Amerika +1.800.753.9221 Option 1 – Customer Care Option 2 – Technical Support	Europa Netherlands: +31 800-0200135 France: +33 800 901 793	Europa Germany: 800 1890272 Other Countries: +31 13 5835404	APAC Shanghai: + 86 21 2412 1618/19 Sydney: +61 2 9751 8500
---	--	--	--