

FS SPACER CLAMP, 80–100 MM

CATALOG NUMBER

FS80-100



CERTIFICATIONS



FEATURES

Provides support for nVent ERIFLEX Flexibar and insulated braided conductors without damaging the insulation

Ensures correct spacing for optimum cooling

Supports up to four conductors in parallel

Eenvoudig te plaatsen

Spacers are halogen free

RoHS compliant

PRODUCT ATTRIBUTES

Article Number: 553580

Finish: Elektrolytisch gegalvaniseerd

Material: Steel;Polyamide

Working Temperature: -40 to 130 °C

Flammability Rating: UL® 94HB

Conductor Width: 80 – 100 mm


Height: 140 mm

Length: 224 mm
Hole Size: 8.50 mm
A: 200 mm
Unit Weight: 0.250 kg

ADDITIONAL PRODUCT DETAILS

Recommended distance between supports is 400 mm (15 3/4").

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

Noord-Amerika	Europa	Europa	APAC
+1.800.753.9221	Netherlands:	Germany:	Shanghai:
Option 1 – Customer Care	+31 800-0200135	800 1890272	+ 86 21 2412 1618/19
Option 2 – Technical Support	France:	Other Countries:	Sydney:
	+33 800 901 793	+31 13 5835404	+61 2 9751 8500