

# Base for universal rotary dimmer with PLC interference suppression 3 - 300 W, 2 wire

310-03901


4 year warranty

Base for a universal rotary dimmer with powerline communication interference suppression, 2 wired, with a capacity of 3 to 300 W. A finishing set XXX-31003 and faceplate in a colour of your choice should be ordered separately.

## Technical data

Base for universal rotary dimmer with PLC interference suppression 3 - 300 W, 2 wire.

- Function: Universal flush-mounting dimmer with rotary control for capacitive, inductive and resistive loads, including dimmable LED lamps. Reverse phase control for resistive and capacitive loads. Phase control for inductive loads. Activate by pressing on the button and adjust by rotating the knob. Can be used in single-pole circuits. When used in two-way or intermediate circuits, the two-way or intermediate switch needs to be replaced by one or more push button extensions (170-0000x) that are wired to this dimmer as indicated in the manual or technical catalogue. Use with or without memory, can be set using the push button input. Minimum dimming level can be set for an optimum dimming range and the avoidance of the flickering or extinguishing of lamps at the minimum dimming level. Non-volatile memory. For use with or without light value memory.
- Minimum load: 3 W
- Maximum load electronic transformer: 300 VA
- Maximum load ferromagnetic transformer: 300 VA
- Maximum load toroidal core transformer: 300 VA
- Hum-free: yes
- PLC interference suppression: this dimmer is equipped with interference suppression of PLC signals (frequency dips up to 3 Hz). This integrated interference suppression attempts to remove as many interfering signals as possible from the mains in order for most lamps to function optimally, without flashing or humming.
- Protection from overload: thermal overload protection. Protection against repetitive overload. Automatic reset function of the protections.
- Short circuit proof: electronic short-circuit protection
- Flush-mounting frame
  - 1 mm-thick metal
  - galvanized on all sides after cutting, even on the cut edges
  - with 4 grooves with screw hole of 7 mm
  - with 4 screw holes (indicated by a screw symbol) with a diameter of 3 mm for mounting on panels
- Fixing method
  - with screws for simple fixing in a flush-mounting box with grip surfaces
- Wire connection
  - the sockets are equipped with screw terminals for clamping the wires.
- End border: The flush-mounting frame is equipped, both on the top and the bottom, with a dark grey, plastic end border. This border is made of PC+ASA and is joined to the flush-mounting frame using a melting process. The corners of the two end borders are equipped with rectangular openings (7.9 x 1.5 mm) each



**niko**

containing a multi-positional snap hook. Thanks to the snap hooks, the 4 rectangular openings ensure that the faceplate can always be attached flat to the wall, even in cases of untidy plasterwork. This works in two directions: If the flush-mounting box sticks out of the plasterwork, the multi-positional snap hooks can compensate for a 1 to 1.2 mm margin; if the flush-mounting box is sunk too deeply in the plasterwork, the snap hooks can compensate for up to a 1.8 mm margin. The end borders also have 4 round openings that ensure the correct positioning of the faceplate in relation to the central plate.

- Input voltage: 230 Vac  $\pm$  10 %, 50 Hz
- Maximum MCB rating: 16 A (limited by national installation rules)
- Connection terminals: 3 connection terminals
- Ambient temperature: -5 – +40 °C
- Impact resistance: The combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Marking: CE

