

# Splashproof double vertical surface-mounting socket outlet 16 A/250 Vac with shutters and pre-wired – includes box with one M20 input with cable gland, screw terminals, black

761-37842

4 year warranty

With this vertical combination, the two splashproof surface-mounting wall sockets are equipped with side earthing, shutters and screw terminals. Both wall sockets are also equipped with a hinged protective cover and are pre-wired (2.5 mm<sup>2</sup>) and mounted in a double, splashproof surface-mounting box with one M20 input with cable gland. The entire unit is splashproof which makes it extremely well-suited for use in damp areas and in demanding environments. Colour combination: black.

## Technical data

Splashproof double vertical surface-mounting socket outlet 16 A/250 Vac with shutters and pre-wired – includes box with one M20 input with cable gland, screw terminals, black. Each socket outlet is covered entirely by a hinged protection cap which opens upward. A spring and a hook-fastener keep the protection cap tightly closed.

- Maximum MCB rating: 16 A (1.5 mm<sup>2</sup>) / 20 A (2.5 mm<sup>2</sup>) (limited by national installation rules)
- Sealing: The cover has an integral closure and is hermetically sealed onto the appropriate box.
- Number of mechanisms: 2
- Material base
  - ureumformaldehyde (UF) with high heat resistance
  - white RAL9010 (approximately)
- Material finishing: The box is made of impact-resistant, dust-preventing, halogen-free and self-extinguishing polypropylene (UL94-V2/1.6 mm). The protection cap is made of rigid ABS.
- Material earthing
  - side earthing in high quality brass
- Material surface-mounting box: The surface-mounting box is made of impact-resistant, dust-resistant, halogen-free and self-extinguishing polypropylene (UL94-V2/1.6 mm).
- Cable space
  - 12.7 mm wiring space under the mechanism
  - mechanism is held by 2 laterally positioned holders in the box
  - a snap connector holds the wired mechanism in place
- Wire connection
  - the sockets are fitted with cage clamps with permanent screws with combination screwheads (Pz2 or slot 1 x 5,5 mm)
  - every screw is provided with a screwdriver slot that prevents the screwdriver from sliding off the screwhead.
- Material earthing: side earthing in high quality brass
- Stripping length
  - 14 mm stripping length
  - indelibly indicated at the rear side: stripping length
- Surface-mounting box: The socket outlets are mounted in a double vertical splashproof surface-mounting box with one M20 inlet for the flush-mounting of two devices. The socket is supplied with one M20 cable



**niko**

gland. Each socket outlet has an integral closure and is hermetically sealed onto the double box. The fixation points of this double, vertical box are situated 120 mm apart on a vertical axis. This size indication is indelibly imprinted on the bottom of each box. The oval screw openings allow for imprecise drilling. By forming a pressure lock, a gasket ensures the protection degree and the double insulation. The box contains two diagonal, knock-out condensation openings.

- Protection degree: IP55 for the combination of a socket outlet and a splashproof mounting box
- Impact resistance: The combination of a Hydro mechanism and a flush- or surface-mounting box has an impact resistance of IK07 with a minimum temperature of -25 °C and a maximum temperature of 55 °C
- Colour: The base material is coloured in mass, black (RAL 9005)
- Certification marks: KEMA
- Marking: CE

$\frac{h_V}{2}$  16 A  
250 Vac

