Motion detector M34LR, KNX®, 5 channels, 39-41 m, IP40, for flush-mounting box, black

350-34013

This motion detector with 5 channels is suitable for KNX® systems. It can be installed in a flush-mounting box. Spring clips for flush-mounting and a surface-mounting box can be ordered separately. In conformity with the European directive for EMC and safety EN 60669-2-1. Finishing colour: black


Compatible secondary detectors: 350-34013

- High performance (up to 41 m)
- Plug-in terminals for fast installation
- Easy configuration (well-structured ETS file)
- 5 channels
- Various applications: presence, lux, constant light switch, HVAC, alarm
- IP40
- For flush-mounting box, flush or surface mounting via accessories





Detection range



Н	Α	В	С
_	Walking	Across	Towards
<u></u>	Å	\(\hat{N}\) →	n̂↑
2.5 m	Ø 39 m	Ø 26 m	Ø 6 m
3.0 m	ø 41 m	ø 27 m	ø7 m

Measured according to EN/IEC63180















flushmounting




Technical data

Article number	350-34013	
Compatible secondary detectors	350-34013	
Input voltage	30 Vdc via KNX®-bus	
Detector output	KNX®	
Maximum power consumption	0.3 W	
Maximum current consumption	10 mA	
Light intensity range	10 lux – 2000 lux	
Number of channels	5 channels: channel 1-3 for adjustable control, channel 4 for	
	HVAC and channel 5 for light measurement	
Switch-off delay	1 s – 18 h 12 min 15 s	
Detection angle	360 °	
Detection range (PIR)	ø 41 m from a height of 3 m	
Ambient temperature	-20 − +50 °C	
Mounting method	flush-mounting box	
Mounting height	2-3 m	
Drill diameter	56 mm	
Minimum flush-mounting depth	17 mm	
Colour	black (approximately RAL 9011)	
Dimensions visible (HxWxD)	111 x 111 x 53 mm	
Dimensions (HxWxD)	111 x 111 x 70 mm	
Protection degree	IP40	
Impact resistance	IK02	
Modification of settings	ETS software	
Marking	CE	

Accessories

390-34103	Surface-mounting box for M34LR, white
390-34113	Surface-mounting box for M34LR, black
390-34203	Flush-mounting box with spring clips for M34LR/M34HC, black

Dimensions



Wiring diagram

