



4L0606

HBI 400 Ledology 6W IP65 (non) maintained AutoTest

Lumen flux 220 lm in case of mains failure



HBI Bisscheroux b.v.
Hofdwarsweg 14
NL-6161 DD Sittard-Geleen

T+31 (0)46 475 65 72
F+31 (0)46 474 04 78
info@hbi-lighting.com
www.hbi-lighting.com

ABN-AMRO
NL02ABNA0619802782
BIC ABNANL2A

BTW/VAT NL 8145.92.351.B01
KvK 14085510

Spacingtabel 1 lux (m)

Hight (m)				
2,0	3,8	10,5	7,2	2,9
2,5	3,6	10,8	7,9	3,1
3,0	3,6	10,7	8,4	3,2
3,5	3,6	10,5	8,8	3,3
4,0	3,6	10,4	9,1	3,3
4,5	3,7	10,4	9,2	3,3
5,0	3,7	10,5	9,3	3,3
5,5	3,5	10,4	9,3	3,0
6,0	3,2	10,4	9,3	3,0
6,5	3,0	10,3	9,1	3,0
7,0	3,0	10,2	9,0	3,0
7,5	3,0	10,0	8,8	3,0
8,0		9,6	8,5	
8,5		8,5	7,6	
9,0		6,9	6,1	
9,5		5,7	5,1	
10		4,6	3,9	
10,5		3,2	2,4	