


Category (ETIM):	Device mounts
Type:	Device mount IP54-SDGS LED
Order number:	18462016600
Configuration:	Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10
Operating device:	Electronic driver DALI (1 pcs.)
Mains voltage:	230V / 50Hz
System performance (W):	52
Luminaire luminous flux (lm):	7000
lm/W:	138
Energy efficiency class:	A+
Ambient temperatures:	/ 35°C
Certifications:	IP 54, protection class I, F, D, DIN10500/Food, Indoor, CE
Colour of the housing:	traffic white RAL 9016
Weight (net) (kg):	2
Dimensions LxWxH/DxH (mm):	1531 x 55 x 43
mounting method:	Mounting rail system mounting
EAN-number:	4020863286317
Commodity code:	94051098


SDGS LED 7000lm 840 • vw • DALI • 18462016600



Lighting technology
open distribution-general diffuse
SDGS LED 7000 lm 840



ηLB	100 %
lm/W	138
Φ ↓/↑	100 % / 0 %
UGR q/l	27.7 / 28.8



Quick-fit mounting system Device mounts; Device mount made of galvanised, profiled sheet steel, surface coated with polyester resin enamel. Toolless fastening with two integrated rotary catches. LED unit made of naturally anodised extruded aluminium profile with end faces made of plastic. Suitable for the mounting of LED light directing components. End faces made of plastic, all-round closed seal to mounting rail. Housing colour traffic white RAL 9016; Direct, general diffuse light distribution. LED diffuser cover made of polycarbonate. Heat-resistant cables including fixed 3-pole rapid installation plug connector with tool-free phase preselection and locating finger. Can be combined with the self-supporting specular reflectors SDFA LED, SDFB LED, SDFT LED und SDFH LED.

Dimensions LxWxH/DxH (mm): 1531 x 55 x 43
Configuration: Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10
Luminaire luminous flux (lm): 7000
lm/W: 138
Operating device: Electronic driver DALI (1 pcs.)
System performance (W): 52
Energy efficiency class: A+
Conditions: Suitable for use in ambient temperatures of 0°C to 35°C
Certifications: IP 54, protection class I, F, D, DIN10500/Food, Indoor, CE

Regiolux GmbH
Type: SDGS LED 7000 840 DALI vw
Article number: 18462016600
Product deep link: <http://www.regiolux.de/de/article/18462016600>
5 year guarantee after registration on website.