## **Datasheet**



Category (ETIM): Control unit

Type: DALI signal Compact control devices-LC-OM DALIeco

 Order number:
 84501039100

 Mains voltage:
 230V / 50Hz


Certifications: IP 20, protection class II, Indoor, CE

Weight (net) (kg): 0.05

Dimensions LxWxH/DxH (mm): 118 x 30 x 21

mounting method: Hollow space mounting
EAN-number: 4020863291519
Commodity code: 85371099

## LC-OM DALIeco • 84501039100



Light/presence control unit for cavity / luminaire installation

2-channel control unit for daylight and presence-dependent control of up to 32 DALI units, connection of up to 4 light and presence sensors; predefined function modes for simplified commissioning; individual adjustment of the function parameters using IR remote control; automatic and manual specification of the setpoint regulation value; 100 h burn-in function for low-pressure fluorescent lamps; operation using standard buttons and IR remote control; housing is intended for recessed installation in cavities such as suspended ceilings or possibly also in luminaire housings. A light/presence sensor for operation of the control (e.g. LC-OM LS/PD LI DALIeco) is also required. Optional remote controls (LC-OM MASTER Remote or LC-OM USER Remote).

Dimensions LxWxH/DxH (mm): 118 x 30 x 21 Certifications: IP 20, protection class II, Indoor, CE

Regiolux GmbH Type: LC-OM DALleco Article number: 84501039100

Product deep link: http://www.regiolux.de/de/article/84501039100