


|                               |                                                                                                                        |
|-------------------------------|------------------------------------------------------------------------------------------------------------------------|
| Category (ETIM):              | Variable device mount                                                                                                  |
| Type:                         | Device mount IP20-SDGVL LED                                                                                            |
| Order number:                 | 18210306650                                                                                                            |
| Configuration:                | Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10 |
| Operating device:             | Electronic driver DALI (1 pcs.)                                                                                        |
| Mains voltage:                | 230V / 50Hz                                                                                                            |
| System performance (W):       | 32                                                                                                                     |
| Luminaire luminous flux (lm): | 4400                                                                                                                   |
| lm/W:                         | 136                                                                                                                    |
| Energy efficiency class:      | A++                                                                                                                    |
| Ambient temperatures:         | 10°C / 45°C                                                                                                            |
| Certifications:               | IP 20, protection class I, F, Indoor, CE                                                                               |
| Colour of the housing:        | traffic white RAL 9016                                                                                                 |
| Weight (net) (kg):            | 2.5                                                                                                                    |
| Dimensions LxWxH/DxH (mm):    | 1531 x 55 x 43                                                                                                         |
| mounting method:              | Mounting rail system mounting                                                                                          |
| EAN-number:                   | 4020863304790                                                                                                          |
| Commodity code:               | 94051098                                                                                                               |


## SDGVL LED 4400lm 840 • vw • DALI • 18210306650



**Lighting technology**  
open distribution-general diffuse  
SDGVL LED 4400 lm 840



|         |             |
|---------|-------------|
| ηLB     | 100 %       |
| lm/W    | 136         |
| Φ ↓/↑   | 100 % / 0 % |
| UGR q/l | 25.1 / 26.1 |



Quick-fit mounting system Variable device mount; Device mount with two lateral lever locks, made of galvanised, profiled sheet steel; surface coated with polyester resin enamel; LED unit made of natural anodised extruded aluminium profile, in housing length for optically seamless light run, end faces made of plastic; can be positioned variably in light run. Suitable for the mounting of LED light directing components. Housing colour traffic white RAL 9016; Light distribution direct as open distribution, matt LED diffuser cover made of polycarbonate. For optically seamless light run design. Heat-resistant cables including connection cable 1 m and rapid installation plug connector with tool-free phase preselection and locating finger. Can be combined with the self-supporting specular reflectors SDFAL LED, SDFBL LED and SDFTL LED.

Dimensions LxWxH/DxH (mm): 1531 x 55 x 43  
Configuration: Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10  
Luminaire luminous flux (lm): 4400  
lm/W: 136  
Operating device: Electronic driver DALI (1 pcs.)  
System performance (W): 32  
Energy efficiency class: A++  
Conditions: Suitable for use in ambient temperatures of 10°C to 45°C  
Certifications: IP 20, protection class I, F, Indoor, CE

Regiolux GmbH  
Type: SDGVL LED 4400 840 DALI vw  
Article number: 18210306650  
Product deep link: <http://www.regiolux.de/de/article/18210306650>  
5 year guarantee after registration on website.