Datasheet

REGIOLUX

Category (ETIM): Suspended luminaire
Type: procube-CUHX LED
Order number: 60433026660

Configuration: Lamps integrated: LED, Light colour 840/neutral white

(4000K), Colour rendering Ra>80; LED service life

50000h L80/B10

Operating device: Electronic driver DALI (1 pcs.)

Mains voltage:230V / 50HzSystem performance (W):42Luminaire luminous flux (Im):4000Im/W:96Energy efficiency class:A+

Certifications: IP 20, protection class I, BAP 65°<1500, F, Indoor, CE

Colour of the housing: traffic white RAL 9016

Weight (net) (kg): 3.357

Dimensions LxWxH/DxH (mm): 1479 x 109 x 43


mounting method: Suspended single mounting, Suspended / light run

mounting, Light structure

EAN-number: 4020863306671 Commodity code: 94051098 procube-CUHX/1500-1 LED 4000lm 840 • vw • DALI • 60433026660



Lighting technologyMicro-parabolic louvre, silky matt-direct distribution CUHX/1500-1 LED 4000 lm 840



Suspended luminaire; Sheet steel housing, compact rectangular cross section, installation height 40 mm; prepared for fixing of end faces or luminaire connectors made of steel. Housing colour traffic white RAL 9016; Direct light distribution using reflectivity-enhanced aluminium parabolic louvre, silk matt with low installation height cross blades, for workstations, "65 < 1000 cd/m² omnidirectional glare suppression according to the current DIN EN 12464-1 standard, self-engaging, louvre is optically seamless for light run mounting; Electrical connection and connection of control cable using 5-pole connection terminal with plug-in contacts. Required accessories: order end faces, connectors, through-wiring and Y-wire-rope suspensions SAY-KS/SAYE-KL with 2000 mm suspension length separately according to luminaire arrangements.

Dimensions LxWxH/DxH (mm): 1479 x 109 x 43

Configuration: Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour

rendering Ra>80; LED service life 50000h L80/B10

Luminaire luminous flux (lm): 4000

Im/W: 96

Operating device: Electronic driver DALI (1 pcs.)

System performance (W): 42 Energy efficiency class: A+

Certifications: IP 20, protection class I, BAP 65°<1500, F, Indoor, CE

Regiolux GmbH

Type: procube-CUHX/1500-1 LED 4000 840 DALI vw

Article number: 60433026660

Product deep link: http://www.regiolux.de/en/article/60433026660

5 year guarantee after registration on website.

