Datasheet

REGIOLUX

Category (ETIM): Suspended luminaire Type: visula-VSHIMP LED 43221016675 Order number:

Configuration: Lamps integrated: LED, Light colour 840/neutral white

(4000K), Colour rendering Ra>80; LED service life

50000h L80/B10

Electronic driver DALI (1 pcs.) Operating device:

Mains voltage: 230V / 50Hz System performance (W): 54 Luminaire luminous flux (lm): 4900 90 Energy efficiency class:

IP 20, protection class I, BAP 65°<3000, F, Indoor, CE Certifications:

Colour of the housing: aluminium natural anodized

Weight (net) (kg):

Dimensions LxWxH/DxH (mm): 1199 x 330 x 30


mounting method: Suspended single mounting

EAN-number: 4020863304424 94051098 Commodity code:


visula-VSHIMP/1200 LED 4900lm 840 • aen • DALI • 43221016675




Lighting technology Diffuser, micro-prismatic-direct/indirect distribution VSHIMP/1200 LED 4900 Im 840



100 % $\eta L B$ lm/W 90 84 % / 16 % Φ 1/↑ ŪĞR q/I 18.1 / 18.2 BAP 65° < 3000cd/m²





Suspended luminaire; Ultra-flat luminaire housing, extruded aluminium profile, naturally anodised, visible installation height 30 mm; end faces and side parts made of naturally anodised aluminium with continuous longitudinal groove, rounded towards the bottom of the luminaire. Housing colour aluminium natural anodized; Direct/indirect light distribution, direct component using microprism made of PMMA, homogeneous light emission through lateral LED light coupling and overlying aluminium reflector with highly reflective white coating, with micro-perforation for the indirect light component; for workstations, omnidirectional glare suppression according to the current DIN-EN 12464-1 standard. Integrated LED driver design. Electrical connection via integrated transparent connection cable 5 x 0.75 mm 2 , length 2300 mm, stripped cable ends. Suspension included

Dimensions LxWxH/DxH (mm): 1199 x 330 x 30

Configuration: Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10

Luminaire luminous flux (lm): 4900

Im/W: 90

Operating device: Electronic driver DALI (1 pcs.)

System performance (W): 54 Energy efficiency class: A+

Certifications: IP 20, protection class I, BAP 65°<3000, F, Indoor, CE

Regiolux GmbH

Type: visula-VSHIMP/1200 LED 4900 840 DALI aen

Article number: 43221016675

Product deep link: http://www.regiolux.de/en/article/43221016675

5 year guarantee after registration on website.