Datasheet

REGIOLUX

Category (ETIM): Suspended luminaire
Type: hokal-HLHIG LED
Order number: 60511024185

Configuration: Lamps integrated: LED, Light colour 840/neutral white

(4000K), Colour rendering Ra>80; LED service life

50000h L80/B10

Operating device: Electronic driver (1 pcs.)

Mains voltage:230V / 50HzSystem performance (W):29Luminaire luminous flux (Im):2300Im/W:77Energy efficiency class:A+

Certifications: IP 20, protection class I, ENEC10 VDE, F, Indoor, CE

Colour of the housing: silver-grey

Weight (net) (kg): 3.2

Dimensions LxWxH/DxH (mm): 1176 x 85 x 72

mounting method: Suspended single mounting, Suspended / light run


mounting

EAN-number: 4020863319077 Commodity code: 94051098

hokal-HLHIG/1200 LED 2300lm 840 • sg • ED • 60511024185



Lighting technologyDiffuser, satined-direct/indirect distribution
HLHIG/1200 LED 2300 lm 840



Suspended luminaire; Sheet steel housing with square design; prepared for fixing end faces or luminaire connectors made of steel; Housing colour silver-grey; Direct/indirect light distribution; glare suppression using diffuse distribution frosted polycarbonate profile; diffuser is optically seamless for light run mounting; Electrical connection via 3-pole connection terminal with plug-in contacts. Required accessories: order face ends, connectors, throughwiring and Y-wire suspensions SAY-KS/SAYE-KL with 2000 mm suspension length separately according to luminaire arrangements.

Dimensions LxWxH/DxH (mm): 1176 x 85 x 72

Configuration: Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour

rendering Ra>80; LED service life 50000h L80/B10

Luminaire luminous flux (lm): 2300

Im/W: 77

Operating device: Electronic driver (1 pcs.)

System performance (W): 29 Energy efficiency class: A+

Certifications: IP 20, protection class I, ENEC10 VDE, F, Indoor, CE

Regiolux GmbH

Type: hokal-HLHIG/1200 LED 2300 840 ET sg

Article number: 60511024185

Product deep link: http://www.regiolux.de/en/article/60511024185

5 year guarantee after registration on website.

