


|                               |                                                                                                                        |
|-------------------------------|------------------------------------------------------------------------------------------------------------------------|
| Category (ETIM):              | Suspended luminaire                                                                                                    |
| Type:                         | stail-SHLPI LED                                                                                                        |
| Order number:                 | 60334024190                                                                                                            |
| Configuration:                | Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10 |
| Operating device:             | Electronic driver (1 pcs.)                                                                                             |
| Mains voltage:                | 230V / 50Hz                                                                                                            |
| System performance (W):       | 58                                                                                                                     |
| Luminaire luminous flux (lm): | 6700                                                                                                                   |
| lm/W:                         | 114                                                                                                                    |
| Energy efficiency class:      | A+                                                                                                                     |
| Certifications:               | IP 20, protection class I, BAP 65°<3000, F, Indoor, CE                                                                 |
| Colour of the housing:        | traffic white RAL 9016                                                                                                 |
| Weight (net) (kg):            | 5.3                                                                                                                    |
| Dimensions LxWxDxH (mm):      | 1540 x 198 x 37                                                                                                        |
| mounting method:              | Suspended single mounting, Suspended / light run mounting                                                              |
| EAN-number:                   | 4020863322497                                                                                                          |
| Commodity code:               | 94051098                                                                                                               |

**stail-SHLPI/1500-2 LED 6700lm 840 • vw • ED • 60334024190**




## Lighting technology

Diffuser, micro-prismatic-direct/indirect distribution  
SHLPI/1500-2 LED 6700 lm 840



|         |                 |
|---------|-----------------|
| ηLB     | 100 %           |
| lm/W    | 114             |
| Φ ↓/↑   | 40 % / 60 %     |
| UGR q/l | 13.6 / 14.2     |
| BAP     | 65° < 3000cd/m² |



Suspended luminaire; Sheet steel housing, flat rectangular cross section, visible installation height 26 mm, steel end faces, prepared for light run installation; Housing colour traffic white RAL 9016; Direct/indirect light distribution using micro prismatic glass, for workstations, 65° < 3000 cd/m² omnidirectional glare suppression according to current DIN-EN 12464-1 standard; Electrical connection via 3-pole connection terminal with plug-in contacts. Required accessories: Y-wire suspension for/without electrical connection must be ordered separately. Recommended minimum pendant length 0.5 m.

Dimensions LxWxDxH (mm): 1540 x 198 x 37  
Configuration: Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10  
Luminaire luminous flux (lm): 6700  
lm/W: 114  
Operating device: Electronic driver (1 pcs.)  
System performance (W): 58  
Energy efficiency class: A+  
Certifications: IP 20, protection class I, BAP 65°<3000, F, Indoor, CE

Regiolux GmbH  
Type: stail-SHLPI/1500-2 LED 6700 840 ET vw  
Article number: 60334024190  
Product deep link: <http://www.regiolux.de/en/article/60334024190>  
5 year guarantee after registration on website.

