


Category (ETIM):	Suspended luminaire
Type:	cubus-RSAXHC LED
Order number:	65240016660
Configuration:	Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra=80; LED service life 50000h L80/B10
Operating device:	Electronic driver DALI (1 pcs.)
Mains voltage:	230V / 50Hz
System performance (W):	24
Luminaire luminous flux (lm):	3200
lm/W:	133
Energy efficiency class:	A+
Certifications:	IP 20, protection class I, BAP 65°<1000, F, Indoor, CE
Colour of the housing:	traffic white RAL 9016
Weight (net) (kg):	4.05
Dimensions LxWxH/DxH (mm):	1188 x 140 x 64
mounting method:	Suspended single mounting, Suspended / light run mounting
EAN-number:	4020863281329
Commodity code:	94051098


cubus-RSAXHC-1200 LED 3200lm 840 • vw • DALI • 65240016660



Lighting technology
Parabolic louvre, silky matt-direct distribution
RSAXHC-1200 LED 3200 lm 840



ηLB	100 %
lm/W	133
Φ ↓/↑	100 % / 0 %
UGR q/l	15.5 / 19.0
BAP	65° < 1000cd/m²



Suspended luminaire; Sheet steel housing, rectangular cross-section, plastic end faces with integrated light run connectors; Housing colour traffic white RAL 9016; Direct light distribution using reflectivity-enhanced anodised aluminium parabolic louvre, silk matt, 65° < 1000 cd/m², omnidirectional glare suppression according to the current DIN EN 12464-1 standard, self-engaging, can be folded down on both sides, louvre is optically seamless for light run mounting; neutral white light colour (840) with very good colour consistency and high colour rendering Ra>80; Electrical connection via 5-pole connection terminal with plug-in contacts. Y-wire-rope suspensions SAY KS/SAYE-KL, suspension length 2000 mm must be ordered separately for the suspension. One SAB suspension bracket per luminaire joint in addition for light run mounting.

Dimensions LxWxH/DxH (mm): 1188 x 140 x 64
Configuration: Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra=80; LED service life 50000h L80/B10
Luminaire luminous flux (lm): 3200
lm/W: 133
Operating device: Electronic driver DALI (1 pcs.)
System performance (W): 24
Energy efficiency class: A+
Certifications: IP 20, protection class I, BAP 65°<1000, F, Indoor, CE

Regiolux GmbH
Type: cubus-RSAXHC-1200 LED 3200 840 DALI vw
Article number: 65240016660
Product deep link: <http://www.regiolux.de/en/article/65240016660>
5 year guarantee after registration on website.

