


Category (ETIM):	Recessed luminaire
Type:	protection-PREO LED
Order number:	72560016680
Configuration:	Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10
Operating device:	Electronic driver DALI (1 pcs.)
Mains voltage:	230V / 50Hz
System performance (W):	37
Luminaire luminous flux (lm):	3900
lm/W:	104
Energy efficiency class:	A+
Certifications:	IP 54, protection class I, F, F-roof, DIN10500/Food, Indoor, CE
Colour of the housing:	traffic white RAL 9016
Weight (net) (kg):	5.3
Dimensions LxWxH/DxH (mm):	597 x 597 x 89
Depth (mm):	82
Ceiling system:	Ceilings with visible T-rails [s-TS] (600x600mm), Concealed symmetrical rail construction [VS] (600x600mm), cut-out ceilings [AD] (600x600mm), cut-out ceilings [AD]
Necessary depth min. (mm):	150(AD); 250(s-TS); 150(s-TS min); 150(VS)
Ceiling cut-out LxW/D (mm):	585 x 585
mounting method:	Ceiling recessing single mounting
EAN-number:	4020863289349
Commodity code:	94051098


protection-PREO/600 IP54 LED 3900lm 840 • vw • DALI • 72560016680



Lighting technology
Diffuser, opal-direct distribution
PREO/600 IP54 LED 3900 lm 840



ηLB	100 %
lm/W	104
Φ ↓/↑	100 % / 0 %
UGR q/l	21.1 / 21.2



Recessed luminaire; Sheet steel housing suitable for ceilings with visible T rails, concealed symmetrical rail constructions and recessed ceilings; protection rating refers to visible luminaire surface; Housing colour traffic white RAL 9016; Direct light distribution using opal diffuser made of acrylic glass with natural anodised aluminium frame; neutral white light colour (840) with very good colour consistency and high colour rendering Ra>80; Electrical connection and connection of control cable using 5-pole connection terminal with plug-in contacts. UBB universal mounting brackets for concealed symmetrical rail constructions or recessed ceilings and SCT CLIPS locking clips for ceilings with visible T rails: please order separately. A vacuum lifting pad SH 55 is needed to draw off the sealing frame.

Dimensions LxWxH/DxH (mm): 597 x 597 x 89
Ceiling system: Ceilings with visible T-rails [s-TS] (600x600mm), Concealed symmetrical rail construction [VS] (600x600mm), cut-out ceilings [AD]
Necessary depth min. (mm): 150(AD); 250(s-TS); 150(s-TS min); 150(VS)
Ceiling cut-out LxW/D (mm): 585 x 585
Configuration: Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10
Luminaire luminous flux (lm): 3900
lm/W: 104
Operating device: Electronic driver DALI (1 pcs.)
System performance (W): 37
Energy efficiency class: A+
Certifications: IP 54, protection class I, F, F-roof, DIN10500/Food, Indoor, CE

Regiolux GmbH
Type: protection-PREO/600 IP54 LED 3900 840 DALI vw
Article number: 72560016680
Product deep link: <http://www.regiolux.de/en/article/72560016680>
5 year guarantee after registration on website.

